

N2H

Android Total Station

| SPECIFICATIONS | | |
|--|-------------------------------|---|
| Distance Measurement with Reflector | Range *1 | 5000m |
| | Accuracy | ±(2+2ppm.D)mm |
| | Measure Interval | Fine: 0.3s, Tracking: 0.1s |
| Distance Measurement without Reflector | Range *2 | 1000/1500/2000m Optional |
| | Accuracy | 0~500m: ±(3mm + 2 x 10-6.D) |
| | | 500~1000m: ±(5mm + 2 x 10-6.D) |
| | | 1000~2000m: ±(10mm + 2 x 10-6.D) |
| | Measure Interval | 0.3-3s |
| Angle Measurement | Accuracy | 2" |
| | Measure Method (HZ/V) | Absolute Continuous, Diametrical |
| | Diameter of Encoder Disk | 79mm |
| | Display Resolution | 0.1"/1"/5" (Optional) |
| | Compensation | Liquid, Dual Axis Compensation |
| | Compensator Setting Accuracy | 1" |
| | Compensator Range | ±4'/±6'(Optional) |
| Telescope | Image | Erect |
| | Tube Length | 154mm |
| | Effective Aperture | 45mm (EDM:50mm) |
| | Magnification | 30X |
| | Resolving Power | 3" |
| | Field of View | 1°30" |
| | Focusing Range | 1.4m |
| | Reticle | Illuminated, 4 Brightness Level |
| Vial | Plate Vial | 30"/2mm |
| | Circular Vial | 8'/2mm |
| Laser Plummet (Default) | Type | Laser Point, 4 Brightness Level |
| | Accuracy | ±1.5mm at 1.5M Instrument Height |
| | Wavelength | 630-670nm |
| | Laser Class | Class 2 /IEC60825-1 |
| | Laser Power | <0.4mW |
| Guide Light | Type | LED |
| | Wavelength | Red 635nm/ Green 590nm |
| | Effective Range | 200m |
| System Config | Operating System | Android 11.0 |
| | Processor | MT6762 |
| | Internal Memory | RAM: 4GB; ROM: 64GB |
| Communication | Interfaces | -Micro SIM |
| | | -USB Type C (OTG) |
| | | -TF Card |
| | Network | 3G 2100/900 CDMA BC0 TDSCDMA A/F |
| | | 4G LTE band1/3/7/38/39/40/41 |
| | Bluetooth | Bluetooth 4.0 |
| | WLAN | Dual-Band Single Stream 802.11 a/b/g/n RF for Data Link |
| | Microphone / Speaker | Available |
| Display | Type | 5.0 Inch, TFT LCD Screen, 720*1280, Alphanumeric keyboard |
| Battery | Type | Lithium-Ion, 7.4V |
| | Operating Time | 8 Hours |
| Dimension | Size | 215mm*170mm*350mm |
| | Weight | 5.95kgs |
| Environmental | Temperature Range (Operation) | -20°C ~ 60°C |
| | Protection | IP55 |

*1: Good conditions (good visibility approx.40km, overcast, twilight)

*2: White objects with high reflectivity (KGC 90%)



- New! Android 11.0 Operating System
- Reliable EDM - 2000m Non-Prism Range
- High Precision - 2", 2+2ppm
- User Friendly with EDM Trigger Key
- 5.0 Inches Color Touchscreen
- Fast, Simple and Flexible Data Transfer
- Intuitive Onboard Software - Survey Star



Android Total Station N2H

With the proven dual-laser technology, N2H features a powerful and reliable EDM module designed for extremely long-range, fast speed and stable measurement, even under the tough conditions.

All these combined in the new-designed colorful touch screen with fast, simple and flexible data transfer, which makes you more productive than ever before.

Reliable and Outstanding EDM

- 1000m/1500m/2000m Non-prism Range Optional.
- 5000m Prism Range.
- Improved the Algorithm by Dual-Laser EDM.

Guaranteed High Precision

- 2" Angle Accuracy.
- 2+2ppm Distance Accuracy.
- Extremely Fast (0.3s) When Getting the Target.

EDM Trigger Key

- Achieve the Target by Only One Simple Button Press.
- Not Necessary to Taking Your Eyes Off the Telescope.

New Designed Control Panel

- 5.0 Inch Color Touchscreen for Higher Readability.
- User-Defined Numeric and Functional Keys.
- Unique Brightness Sensor with Virtual Button, Which Provides a Smartphone-like Experience.

Fast, Simple and Flexible Data Transfer

- Support USB-Type C, TF Card, SIM Card Slot
- Flexible Data Transfer with Bluetooth and Wi-Fi Technology.

Reliable and Outstanding EDM - 2000m Non-Prism

Guaranteed High Precision - 2", 2+2ppm

User Friendly - EDM Trigger Key

Smartphone-like Experience - Brightness Sensor with 5.0 Inch Touchscreen

Fast, Simple and Flexible Data Transfer



Digitizing Your Work by Survstar

Iconic User Interface

The Survstar onboard program features an iconic display of the survey elements, like electronic bubble, e-compass, star key and iconic toolbar. It provides a better understanding for station setup, data collect, stake out in daily tasks.

Map-Driven Workflow

Map is an interactive display feature embedded in Survey Star. It offers a graphical display of the survey elements with base map, which can be downloaded by network, or imported by manual. It provides a better understanding for data collect, stake out in daily tasks.

Powerful Onboard Program

Including Free Station, COGO, CAD Stake Out, Arc Stake Out, Reference Line, Traverse, Roads, etc.

CAD Stake Out

With CAD Stake Out, N2H helps to handle the data and stake out freely in DWG or DXF files. The only thing you need to do is import the CAD files to your N2H total station.

Traverse

When you've got a very difficult site with a lot of obstructions like trees, that obscures our visibility; Or when you can't measure or place the points you need, traverse on N2H total station helps to get a few more control points to work further than the first orientation.

Flexible Data Manage

You can send or receive your data to your controller or PC more flexible than ever, by multiple data format, e.g. *.txt, *.dxf, *.dat, *.csv, *.xls.

When you've got a N2H total station, you will have infinite possibilities.

